

WBM15

SKC Window Film

Advantage -

1. Increase personal privacy
2. Better eye comfort
3. Great maintenance with less scratch
4. Long life indoor fabric from fading

Clear Hard-Coating

Optical Grade PET Film (23±1μm)

Adhesive

Optical Grade PET Film (12±1μm)

UV-Cut PSA

Silicone Release Film(23μm)

Visible Light Transmitted		16%	KS L 2016 ISO 9050
Visible Light Reflected	External	59.2%	KS L 2016 ISO 9050
	Internal	62.9%	
Solar Heat Reduction		74%	KS L 2016
Solar Heat	Reflected	54.4%	ISO 9050
	Absorbed	33%	
	Transmitted	12.6%	
IR Transmitted		9%	ISO 9050
UV Rejected		99%↑	KS L 2514 ISO 9050
Total Solar Energy Rejected (TSER)		79.7%	ISO 9050

Thickness	1.5Mil/2Ply	
Shading Coefficient	0.26	KS L 2016
Solar Heat Gain Coefficient (SHGC)	0.22	KS L 2514
Scratch Resistant	>2H	ASTM D3363
Haze	1.3%	ASTM D1003
Adhesion of Hard-Coated Surface	5B (0% peel-off)	ASTM D3359